

Title: Zimbabwe Module Double Glass 580 Parameters

Generated on: 2026-02-21 10:54:54

Copyright (C) 2026 HALKIDIKI BESS. All rights reserved.

Our modules perform better on sunny and hot days thanks to its optimized temperature coefficient. Our modules can also provide higher power output under low light conditions, such ...

Excellent temperature performance The temperature of HC module is 1.6 °C lower than that of the conventional module under the same working condition, which results less power loss.

Electrical Parameters (STC*) Module Type: SE5-72HBD Maximum power (Pmax/W) Open Circuit Voltage (Voc/V) Short Circuit Current (Isc/A)

Improved light trapping and current collection technology enhance module power output and reliability. Better temperature coefficient half-cell design. Values at Standard Test Conditions STC ...

DEEP BLUE 4.0 C Mono 580W n-type Bifacial Double Glass High Efficiency Mono Module JAM72D40 555-580/GB Series

Nominal bi-facial module gain coefficient can run from 5% to 30% or more, depending on the installation height and the amount of indirect irradiance. It is recommended to design the ...

Founded in 1988, ZNShine solar is a world's leading high-tech PV module manufacturer. With the advanced production lines, the company boasts module capacity of 10 GW.

80 °C; 5% 2.0 mm glass, high transmission, AR coated, tempered POE 2.0 mm white glazed glass, tempered IP68 rated, 3 Bypass Diodes 30 mm anodized Aluminium alloy 1 x 4 mm², 350 mm ...

Website: <https://www.halkidiki-sarti.eu>

